



**D4202-1 SPACER**

Superseded

RELEASED  
2011-12-14  
MP

- NOTES:**
- 1) MATERIAL: 6061-T4/-T42 ALUMINUM TUBING PER WW-T-700/6, AMS 4081, OR ASTM B210 / B221 / B241  
REF DART SPEC M6061T4T0.500W.058  
OR  
6061-T6/-T62 ALUMINUM TUBING PER WW-T-700/6, QQ-A-200/8, QQ-A-225/8, AMS 4080 / 4082, OR ASTM B210 / B221 / B241  
REF DART SPEC M6061T6T0.500W.58  
HEAT TREAT TO -T4/-T42 CONDITION. MIN UTS = 30 KSI (60 HREW MIN)
  - 2) FINISH: NONE
  - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
  - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
  - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
  - 6) IDENTIFICATION: NONE
  - 7) WEIGHT: 0.03 lbs

C	6061-T4 WAS 6061-T6, 0.058 WAS 0.049	CP	11.12.13
B	0.049 WAS 0.058. REASON: FACILITATE MFG	MB	11.03.22
A	NEW ISSUE	CP	10.09.22
REV.	DESCRIPTION	BY	DATE
DESIGN	GP	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	GP		
CHECKED	ASS	DRAWING NO.	REV. C
MFG. APPR.	EF	D4202	SHEET 1 OF 1
APPROVED	TH	TITLE	SCALE
DE APPR.		SPACER	NTS
DATE	11.12.13	COPYRIGHT © 2010 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	